



# Tron 40S MkII



[www.jotron.com](http://www.jotron.com)



## ▶ Tron 40S MkII

Float free and manual GMDSS EPIRB. With new state of the art technology. New non hazardous battery and improved visibility when activated. Fits existing brackets.



SPECIFICATIONS	
<b>TECHNICAL</b>	
Battery:	Lithium metal, 7,2V/7200 mAh, 5 years service life
Dimensions:	
• Height:	379 mm
• Diameter:	180mm
Weight:	2 Kg
Materials:	Glass-reinforced Polycarbonate
Compass safe distance:	1.5m
Temperature range:	-20°C to +55°C (operating) -30°C to +65°C (storage)
Operating life:	Minimum 48 hours at -20°C
Antenna:	Omni directional
Cospas-Sarsat Transmitter	
• Frequency:	406.037 MHz
• Output power:	5W
Homing transmitter	
• Frequency:	121.500 MHz
• Output power:	Up to 100 mW
Protocols:	Maritime, Serialized, Radio Call sign
<b>ACCESSORIES</b>	
Brackets:	Float-free: FB-6
Float-free with heating:	FBH-4
Battery:	Replacement kit
Hydrostatic release:	HRU kit
<b>WARRANTY</b>	5 years

Agent/Distributor:



marinesales@mackaymarine.com  
+1 281 479 1515

service@mackaymarine.com  
+1 281 478 6245

Jotron AS reserves the right to change the design and/or specifications at any time without prior notice. Reservations are also taken towards any general errors that may occur.

v.D

[www.jotron.com](http://www.jotron.com)

## CONTACT INFORMATION

**Jotron AS**  
P.O.Box 54  
3281 Tjodalving  
Norway  
Tel: +47 33 13 97 00  
Fax: +47 33 12 67 80  
sales@jotron.com

**Jotron UK Ltd.**  
Crosland Park  
Cramlington  
NE23 1LA  
United Kingdom  
Tel: +44 (0) 1670 712000  
Fax: +44 (0) 1670 590265  
sales@jotron.com

**Jotron Asia Pte. Ltd.**  
19 Loyang Way  
Changi Logistics Centre  
Rear Office Block 04-26  
Singapore 508724  
Tel: +65 65426350  
Fax: +65 65429415  
sales@jotron.com

**Jotron USA, Inc.**  
10645 Richmond Avenue, Suite 170  
Houston, TX 77042  
USA  
Tel: +1 713 268 1061  
Fax: +1 713 268 1062  
sales@jotron.com