

4000019415

## P-8300 MkII Sound Reception Display Unit

Sound Reception main display unit



MED Certification



- Compatible with IEC61162-450
- Easy installation
- Web-interface
- Amplifies meaningful sounds within a 70-2100 Hz range
- 5 pairs cabling via junction box (optional)
- Adjustable volume and dimmer
- Option for additional slave display units
- Approved according to:
  - MED
  - ISO 14859
  - IEC 60945
  - IEC 61162/2010-1 + 2011-450
  - IEC 62288
- Console Mounted, 24V



Marine Electronics &  
Satellite Communications

[www.mackaymarine.com](http://www.mackaymarine.com)

Created: 30.10.2019, updated: 05.11.2021

page 1/4

[www.zenitel.com](http://www.zenitel.com)

[info@zenitel.com](mailto:info@zenitel.com)

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel - All rights reserved.

## DESCRIPTION

The Phontech Sound Reception Display Unit P-8300 MkII is designed to receive and detect foghorn sounds from other marine vessels in the range of 70-2100 Hz. The P-8300 MkII is for use on-board one-man operated closed bridge class ships.

Connected to an omnidirectional microphone/antenna unit mounted outside of the vessel, the P-8300 MkII main display unit will reproduce and amplify incoming sounds from all directions and indicate the approximate direction of the nearby ship by clear light indications.

By using high capacity microcontrollers and sophisticated software algorithms this digital system has superior performance, both for noise suppression and direction detection. Through the self-calibrating functionality, it is also very easy to install.

The P-8300 MkII main display unit includes a web interface for easy configuration as well as a status (error) indication, control knob for adjustable volume, dimmer and LED test. The WEB interface configuration contains provisions for:

- Error description
- Network settings
- IEC 61162-450 settings
- Syslog settings
- Audio Settings
- Logging events
- Detection direction: Fore/aft (reverse)
- Master/Slave setting
- Direction alignment setting
- Detection Pointer hold time
- Firmware update
- Factory Reset
- Reboot

This P-8300 MkII Sound Reception System is MED-approved and is wheel marked according to MED-B. The unit has DNV/ABS/RMRS/CCS type approvals.

The P-8300 MkII Sound Reception System is also designed to meet;

**SOLAS Chapter V - Safety of navigation - Regulation 19** *Carriage requirements for shipborne navigational systems and equipment.*

**IMO Res. A.694(17)** *General requirements for shipborne radio equipment forming part of the Global Maritime Distress and Safety System (GMDSS) and for electronic navigational aids.*

**IMO Res. MSC.36(63)** *Adoption of the international code of safety for high speed craft (1994).*

**IMO Res. MSC.86(70)** *Adoption of new and amended performance standards for navigational equipment.*

**IMO Res. MSC.97(73)** *Adoption of the international code of safety for high speed craft (2000).*

**IMO Res. MSC.191(79)** *Performance standards for the presentation of navigation-related information on the shipborne navigational displays*

## SPECIFICATIONS

### MECHANICAL

Dimensions (WxHxD)	144x144x124 mm
Weight	0.85 kg
Material	Silicone / Thermoplastic / Sheet metal
Color	RAL 7021 / RAL 7043
Mounting	Flush / Console (optional wall mounting box)
Fixing	4 x M3 bolts
Access	Front
Cable Entry	Rear
Manufacturer	Phontech by Zenitel


### ENVIRONMENTAL

Temperature	-15°C to +55°C
Humidity	+93% (at +40°C)
Ingress Protection	IP-22

### ELECTRICAL

Power Supply	21 – 32 VDC
Power Consumption	8W max, 4W typical
Heat Dissipation	< 8W
Termination	Screw terminals, ≤ 2.5 mm <sup>2</sup>
Compass Safe Distance	> 2.2 m

# TECHNICAL DIMENSIONS



## ACCESSORIES



### WALLBOX FOR CIS

Item number: 4000014256P

## USED WITH



4000019634

### 4000019416 P-8301 MKII MICROPHONE UNIT

Microphone/Antenna Unit



[www.mackaymarine.com](http://www.mackaymarine.com)

**Mackay Marine – High Seas**

+1 281 479 1515 [marinesales@mackaymarine.com](mailto:marinesales@mackaymarine.com)

**Mackay Communications, Satellite Solutions**

+1 919 850 3100 [satserv@mackaycomm.com](mailto:satserv@mackaycomm.com)

**Mackay Marine Canada**

+1 902 469 8480 [sales.canada@mackaymarine.com](mailto:sales.canada@mackaymarine.com)

**Mackay Marine Alaska & Pacific Northwest**

[NWsales@mackaymarine.com](mailto:NWsales@mackaymarine.com) Ballard/AK: 206 282 8080

South Seattle/Tacoma: 253 922 6260