

DECKMA HAMBURG GmbH




15ppm Bilge Alarm OMD-24

According to regulations of IMO Resolution MEPC. 107(49)
U.S. Coast Guard approved



www.deckma.com

We help to protect the Environment



DECKMA HAMBURG GmbH

DECKMA Decksmaschinen und Automation Vertriebsgesellschaft in Hamburg mbH

SPECIFICATION OMD-24

Range:	0 – 30 ppm, Trend up to 50 ppm
Accuracy:	According IMO MEPC. 107(49)
Linearity:	Up to 30 ppm better than $\pm 2\%$
Display:	Graphic Display
Power Supply:	24 V AC or DC +/- 10%
Consumption:	< 5 VA
Alarm Points 1 + 2:	Adjustable between 1 - 15 ppm (Works adjustment 15 ppm)
Alarm 1 Operating Delay: (for annunciation purpose)	Adjustable between 1 – 540 sec. (Works adjustment 2 sec.)
Alarm 2 Operating Delay: (for control purposes)	Adjustable between 1 – 10 sec. (Works adjustment 10 sec.)
System Fault Alarm:	Red LED
Alarm Contact Rating:	Potential free 1-pole change over contacts, 3 A / 240 V
Alarm Indication:	Red LED's
Output Signal:	0 – 20 mA or 4 – 20 mA, reversible ext. Load < 150 Ohm
Sample Water Pressure:	0,1 – 10 bar
Sample Flow:	Approx. 0,1 - 3 l/min. depending to pressure
Ambient Temperature:	+ 1 to + 55° C
Sample Water Temperature:	+ 1 to + 65° C
Roll:	Up to 45°
Size (Computer Unit):	185 mm W x 210 mm H x 65 mm D
Size (Measuring Cell):	140 mm W x 160 mm H x 65 mm D
Degree of Protection:	IP 65
Weight:	2,5 kgs
Pipe Connections:	R 1/4" Female

Contacts / Enquiries:

Agent:

DECKMA HAMBURG GmbH

Phone: +49 (0) 40 54 88 76 -0
Fax: +49 (0) 40 54 88 76 -10
eMail: post@deckma.com
Internet: www.deckma.com

Postal Address: Kieler Strasse 316
22525 Hamburg
Germany

Where to Buy:



**Mackay Marine – New Orleans
Engine Room Department**
+1 504 733 5824 Office
+1 504 734 8535 Fax
jennifer.ory@mackaymarine.com
wanda.adams@mackaymarine.com
calibrations@mackaymarine.com