FURUNO









Records all crucial data to help identify the cause of marine accidents, as well as contribute to the prevention of future accidents

A Voyage Data Recorder (VDR) and Simplified Voyage Data Recorder (S-VDR) are similar to the black boxes carried on aircraft. The VDR/SVDR aids investigators in securing evidence by reviewing procedures and instructions in the moments before an accident. The VDR/SVDR collects data from all interfaced sensors on board the vessel, storing it in an external Data Recording Unit (DRU). The system comes with two tamperproof DRU units, one fixed and one float-free. They are designed to withstand the extreme impact, pressure, shock and heat, which may happen during an incident. When the DRU is retrieved, the stored data can be replayed by authorities to investigate the cause of the accident.



- ► Complies with the IMO performance standards for VDR and S-VDR
 - •Data storing for 48 hours both in fixed and float-free recording medium
 - •Data storing for 30 days/720 hours in SSD in the Data Collecting Unit
- No.1, 2 Radar and main ECDIS display images can be stored
- * Up to 5 display images from FURUNO Radar FAR-3000/FCR-2xx9 series or FURUNO ECDIS FMD-3200/3300 can be stored simultaneously through Ethernet without optional SSD.
- * Radar and ECDIS images can be recorded at 15-second intervals.
- ► Easy to integrate with IBS Network
 - * Radar and ECDIS that utilizes LAN interface based on IEC 61162-450 can be connected through Ethernet.
- ► Video LAN converter can convert the Radar signal (DVI or RGB) into Ethernet
- * Necessary when FURUNO Radar FAR-15x8/FAR- 2xx7, ECDIS FEA-2107/2807 or the products of third-party manufacturers are connected to VR-7000/7000S.

- Optional sensor adapter gathers all the serial/analog/digital sensor data and collectively feeds it to DCU Multiple sensor adapters can be interfaced depending upon the number of sensors to be interfaced.
- "Live Player V5" allows monitoring and playback of collected data on a PC. In adition, remote replay and remote extraction via satellite connection available.
- Extracted data can be saved onto a USB flash memory
- Global customer support and services with FURUNO worldwide service network

■ Simplified Voyage Data Recorder VR-7000S

- Complies with the IMO performance standards for S-VDR, MSC 163(78)
- Applied to S-VDR carriage requirement for existing cargo ships over 3,000GT
- •Selectable DRU: fixed DRU or float-free DRU
- Save function

If marine incidents occur, record the data, which are recorded to the capsule, to the safe storage area for a long term recording by this function.

Easy to input the sensor data and review stored data The onboard sensors can be integrated and interfaced to the VR-7000/7000S thanks to Video LAN converter and sensor adapters. Also, the collected data can be replayed with the PC software or extracted onto a USB flash memory for later analysis. Fixed DRU Float-free DRU VR-70203 VR-7021F* Any Location ** Remote Alarm Panel Live Player V5 VR-7017 VR-7030 Live Player V5 Junction Box for Float-free DRU VR-7022F Ethernet 24 VDC Ethernet ** Requires VSAT antenna etc. 24 VDC, RS-422 Ethernet Ethernet (IEC 61162-450) Switching HUB HUB-100/ Sensors Intelligent HUB HUB-3000 AMS **Data Collecting Unit** 100-230 VAC AIS Ethernet VR-7010 GPS navigator Sensor Adapter Echo sounder Sensor Adapter Sensor Adapter Sensor Adapter Speed log MC-3000S MC-3010A MC-3020D Auto pilot Ethernet Ethernet Ethernet Steering gear (IEC 61162-450) (IEC 61162-450) IEC 61162-1/2 Fire detection Video LAN Converter IF-7100 IEC 61162-1 DVI-D/RGB Standard ----- Option ECDIS 100-230 VAC Chart Radar Local Supply Microphone VR-7011/ VHF Waterproof Microphone Radiotelephone * Select one for VR-7000S VR-7012W

Live Player V5

This software extracts and displays the data recorded in the Data Recording Unit, in real time, on the networked PC screen. In addition, The data can be extracted and displayed remotely on the PC screen anywhere via satellite connection. Also, the data can be replayed for a more thorough data analysis at a later date.



Remote Alarm Panel

At-a-glance recognition of VDR status with minimal operation.





Time of last cha DIET

Secul British SECS. A. 1 OF THE OF THE INC. OF SECS. A. 1 OF THE OF THE INC. OF THE SECS. A. 1 SECS. OF THE INC. OF THE INC. OF THE SECS. A. 1 SECS. OF THE INC. OF THE IN	
MENUTESCI SAIX ENTI STOP	4/▶ Select

System health checking		《Alert List》	
eck ENT Stee	4/▶ Select.	DENDIESCI LIST (ENT) INDUS	-

(serial/analog/digital signals)

SPECIFICATIONS

Product Name		VOYAGE DATA RECORDER / SIMPLIFIED VOYAGE DATA RECORDER		
Data Recording Pe			720 hours	
Collecting Interface		Ethernet (IEC 61162-450)	13 ch (1 ch for PC)	
Unit		Serial (IEC 61162-1/2) Input	2 ch (when interfaced with the MC-3000S,	
(DCU)			4 additional channels can be added)	
		Serial (IEC 61162-1) Input	6 ch (when interfaced with the MC-3000S,	
			4 additional channels can be added)	
		Digital Input	Option (when interfaced with the MC-3020D,	
			8 channels can be added)	
		Analog Input	Option (when interfaced with the MC-3010A,	
			3 channels can be added)	
		Bridge audio	8 ch	
		VHF audio	2 ch	
		Remote Alarm Panel	1 ch	
		24 VDC for Fixed DRU	1 ch	
		24 VDC for Float-free DRU	1 ch	
		24 VDC for Sensor Adapter	1 ch	
		AMS	1 ch	
		(Serial IEC 61162-1 Input/Output)	1 GH	
		AMS (Contact)	Input: 2 ch	
			Output: 3 ch	
		USB	1 ch (for USB flash memory to extract the data only)	
Fixed Data Recording		Memory	32 GB	
Unit (Fixed DRU)*		Recording Period	48 hours	
Float-free Data Recording		Memory	64 GB	
Unit (Float-free DRU)*		Recording Period	48 hours	
Remote Alarm Panel		Display	4.3" color LCD	
Video LAN Converter		Interface	DVI-D/RGB: 2 ch	
			Ethernet: 1 ch	
Sensor Adapter (Serial) Sensor Adapter (Analog) Sensor Adapter (Digital)		al) Interface	IEC 61162-1/2: 4 ch	
			IEC 61162-1: 4 ch	
			Ethernet: 1 ch	
		Interface	Analog Input: 3 ch	
		Interface	Digital Input: 8 ch	
Intelligent	Hub	Interface	Ethernet: 8 ch	
Switching	Hub	Interface	Ethernet: 8 ch	
* Select one for	or VR-7000S	•		

Select one for VR-7000S


POWER SUPPLY

DCU	100-230 VAC: 1.6-0.7 A, 1 phase, 50-60 Hz
Video I AN Converter	24 VDC: 0.7 A

Data Collecting Unit VR-7010

29 kg 63.9 lb fixing hole 2-ø12 310 12.2" 260 10.2" 568 22.4" 516 20.3" 582 22.9"

Video LAN Converter IF-7100



ENVIRONMENT

Ambient	DCU	-15°C to +55°C	
Temperature	Fixed DRU	-25°C to +55°C	
	Float-free DRU	-20°C to +55°C	
	Microphone	-15°C to +55°C	
	Waterproof Microphone	-25°C to +55°C	
	Remote Alarm Panel	-15°C to +55°C	
	Video LAN Converter	-15°C to +55°C	
Relative Hu	midity	95 % at 40°C	
Degree of	DCU	IP20	
Protection	Fixed DRU	IP56 equivalent	
	Float-free DRU	IP67 equivalent	
	Microphone	IP22	
	Waterproof Microphone	IP56	
	Remote Alarm Panel	IP22 (front panel), IP20 (back)	
	Video LAN Converter	IP22 (bulkhead mount),	
		IP20 (tabletop mount)	
Vibration		IEC 60945 Ed. 4	

EQUIPMENT LIST

Standard			
1. Data Collecting Unit (DCU)	VR-7010	1 unit	
2. Remote Alarm Panel	VR-7017	1 unit	
3. Fixed Data Recording Unit (Fixed DRU)*	VR-7020	1 unit	
4. Float-free Data Recording Unit (Float-free DRU)*	VR-7021F	1 unit	
5. Junction Box for Float-free DRU	VR-7022F	1 unit	
6. Video LAN Converter	IF-7100	0~2 units	
7. Microphone	VR-7011	1~8 units	
Waterproof Microphone	VR-7012W ∫	1~0 units	
9. Sensor Adapter (Serial)	MC-3000S	0~2 units	
* Soloct one for VP-7000S			


Option

1. Sensor Adapter (Serial*1/Analog/Digital)	MC-3000S/3010A/3020
2. Video LAN Converter*2	IF-7100
3. Microphone	VR-7011
4. Waterproof Microphone	VR-7012W
5. Intelligent HUB	HUB-3000
6. Switching HUB	HUB-100
7. SSD for DCU	

MC-3000S/3010A/3020D


8. DVI cable

Microphone



Fixed Data Recording Unit


12 0.5




Float-free Data Junction Box **Recording Unit** VR-7021F



Remote Alarm Panel VR-7017



Waterproof Microphone



Beware of similar products

FURUNO ELECTRIC CO., LTD.

All brand and product names are registered trademarks, trademarks or service marks of their respective holders.

143 5.6

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

FURUNO U.S.A., INC. U.S.A. | www.furunousa.com FURUNO PANAMA S.A. FURUNO (UK) LIMITED **FURUNO NORGE A/S**

FURUNO DANMARK A/S FURUNO SVERIGE AB FURUNO FINLAND OY FURUNO POLSKA Sp. Z o.o. FURUNO DEUTSCHLAND GmbH

FURUNO FRANCE S.A.S. FURUNO ESPAÑA S.A. FURUNO ITALIA S.R.L. FURUNO HELLAS S.A. FURUNO (CYPRUS) LTD

FURUNO EURUS LLC FURUNO SHANGHAI CO., LTD. **FURUNO CHINA CO., LTD. FURUNO KOREA CO., LTD FURUNO SINGAPORE**

PT FURUNO ELECTRIC INDONESIA **FURUNO ELECTRIC (MALAYSIA)** SND. BHD. Malaysia | www.furuno.my

> 6-G-1907PDF Catalogue No. CA000001325

