

# Sea Tel Model 5012

3-Axis marine stabilized antenna system compatible with Ku-band satellites

2013 Data Sheet

The most important thing we build is trust

**COBHAM**

## Model 5012

Sea Tel 5012 is a 3-Axis marine stabilized antenna system compatible with most Ku-band satellites. The revolutionary architecture of this 1.24 meter system is based on Sea Tel's industry leading XX09 marine stabilized antenna system. The 5012 is the industry's first 1.24m Ku-band only system powered by integrated marine antenna (IMA) software, supplied in a frequency tuned 1.68m (66") radome. Featuring an integrated control unit (ICU) that offers a single box electronic control solution to maintain the best and most efficient pointing accuracy in

the maritime market. With its extended web based secured user interface, built-in remote management capabilities it offers integration into network management systems through its Media Xchange Point (MXP), first seen on the 4012 system.

The intuitive web user interface accessible from practically any internet-enabled device including mobile devices, with secured socket layer (SSL) password protection, built-in remote management capabilities, multi-level data analysis capability and easy integration into network management systems through

its Media Xchange Point (MXP), make IMA software enabled Sea Tel 5012 ready to face the communications needs of the maritime market in the 21st century.

Sea Tel 5012 is easy to install and designed to meet some of the toughest shock and vibration specifications, such as IEC 60721, IEC 60945 and MIL STD 167-1. The same RF components used in the design of Eutelsat type approved Sea Tel 5009 systems are also used on this antenna system providing unparalleled reliability.

## 5012 Key Benefits

- Easy to install and operate
- Extensive capabilities for online and offline troubleshooting
- Intuitive and secured user interface with extensive data logging capabilities
- Fully IP based "plug and play" architecture
- Meets the high performance threshold set by the Sea Tel 5009
- Mechanically compatible with 5009 spares kits
- Eutelsat and Anatel approval (pending)
- Cylindrical matching radome with Sea Tel's 5004 TVRO antenna 66" radome (Note: 60" standard for 5004)



# Sea Tel Model 5012

3-Axis marine stabilized antenna system compatible with Ku-band satellites



## Typical data for Model 5012

<b>Reflector size</b>	1.24m (50in) D Ring focus
<b>Radome Dimensions</b>	1.71m/67.2in D x 1.77m/70in H (1.8m/71in max flange diameter))
<b>Tx Frequency</b>	13.75-14.5 GHz
<b>Rx Frequency</b>	10.70-12.75 GHz
<b>Tx Gains</b>	43.0dB @ 14.25GHz
<b>Rx Gains</b>	41.6 @ 12.5GHz
<b>G/T (calculated)</b>	20.0 dB/k, Clear Sky, 30° EL
<b>FCC Input Power Spectral Density Limitation</b>	-14.0 dBW/4KHz
<b>BUCs</b>	8W & 16W LBUC, MINI BUC and others
<b>Pedestal Type</b>	3-axis
<b>Azimuth</b>	Unlimited
<b>Elevation Joint Angle</b>	-15° to +115°
<b>Weight</b>	182kg/400lb
<b>Polarization</b>	Linear cross-pol or co-pol (selectable from below deck)
<b>Stability Accuracy</b>	0.1° RMS

## Typical data for Media Xchange Point (MXP)

- Standard 19 Inch 1U rack Mount. (Slide Rails Optional)
- 43 x 43 x 4.35 (cm)/ 17 x 17 x 1.75 (In)
- 110/220VAC, 47-63 Hz, Single Phase
- 3.0 kgs/ 6.6lbs
- 4 Ethernet Ports
- 1 Ethernet Port (Internal, RJ)
- 1 sma Connector (RX from RJ)
- 1 F-Connector from RJ to diplexer)
- 8 Tri colored MXP status LEDs
- USB Device (Mini B)
- 2 RS-232 pass through ports
- 1 NMEA RS-232 serial port
- 1 RS-232 Console Port
- SBS & Synchro Gyro Inputs
- Aux IN1 & Aux IN2
- SW1, SW2, SW3, SW3A, SW4, SW4A (I/O)



marinesales@mackaymarine.com  
+1 281 479 1515

service@mackaymarine.com  
+1 281 478 6245

For further information please contact:

### Cobham SATCOM Maritime Systems

U.S.A. Tel: +1 925-798-7979  
Fax: +1 925-288-1420  
Toll Free: +1-888-798-7979  
E-mail: satcom.concordsales@cobham.com

EUROPE Tel: +44 2380 671155  
Fax: +44 2380 671166  
E-mail: satcom.southamptoneurosales@cobham.com

ASIA Tel: +65 6795-2205  
Fax: +65 6515-6546  
E-mail: satcom.asiasales@cobham.com