

Thales MissionLINK 200 on Iridium Certus



Same dependable and
robust comms, smaller antenna



Thales MissionLINK 200

Thales MissionLINK provides global terrestrial communications coverage, anywhere in the world. Unaffected by weather or landscape, it is the solution to depend on for essential communications wherever your mission takes you. Whether you operate as part of a deployed force or a single individual, this solution is designed to meet your unique challenges through a simple, adaptable and robust design. MissionLINK operates using Iridium Certus broadband services over a network of 66 satellites that cover 100% of the globe. The solution utilizes this robust network service to provide highly reliable, mobile and essential voice, text and web communications for fixed sites and mobile users.



Technical Specifications

Key Features

- Certus 200 Services (176 kpbs Up/Down)
- 100% Global Satellite Coverage and Low Latency for Critical Data and Voice Communications
- Satellite to Land Mobile Radio Extendable Network Through a Unique Radio Gateway
- Easily Integrates Terrestrial Cellular with Built-in Preferred Routing Switch
- Dependable and robust satcoms, covering every continent

Terminal Specifications

Height: 2.3 inches (5.8 cm)

Width: 12 inches (30.5 cm)

Depth: 9 inches (22.9 cm)

Weight: 7.5 pounds (3.4 kg)

Power Options

Option 1: 10–32 VDC

Option 2: AC/DC supply with 12 VDC (65 watt nominal/120 watt max)

IP Rating: IP31

Front Connectors: RJ-45 LAN (3) Class 2 PoE RJ-45 WAN (1) for cellular, VSAT and other IP connections, RJ-14 POTS (2 independent phone lines)

Rear Connectors: DC Power Input (10–32V) MIL-STD-1275D, DC Power Input (+12V Regulated), GPIO (RS-232, +12V out, Emergency, Radio Gateway, Discrete I/O), TNC — RF connection to Antenna, Wi-Fi — Reverse SMA, SIM card slot

Mechanical Vibration and Shock:

MIL-STD-810G w/Change 1, Test Method 514.7, Category 4

Low-gain omnidirectional antenna to enable the fastest upload and download speeds to cover any land communications need from safety services, tracking and location services, out-of-band management to operational reporting and data transfers.

Antenna Specifications

Size: 5 inches dia. x 5.5 inches h (12.5 cm dia. x 14 cm h)

Weight: <0.7 kg/1.5 lbs

Power: Directly powered by the terminal at 24 VDC

IP Rating: IP67

Operating Temperature: -40 to +55° C

Mechanical Vibration and Shock:

MIL-STD-810G w/Change 1, Test Method 514.7, Category 4



www.mackaycomm.com

+1 919 850 3100

satserv@mackaycomm.com

Satellite PTT, Voice & Data Equipment and Airtime

Specifications are subject to change without notice.

Thales Defense & Security, Inc.

22605 Gateway Center Drive | Clarksburg, MD 20871

TF: +1.800.324.6089 | P: +1.240.864.7695

satcomsolutions@thalesdsi.com

www.thalesgroup.com/linksatcom | www.thalesdsi.com



2806:012021:V1

Thales has a policy of continuous development and improvement and consequently the equipment may vary from the description and specification in this document. This document may not be considered as a contract specification. Graphics do not indicate use or endorsement of the featured equipment or service. Copyright © 2021 Thales

