

SAILOR® 1000 XTR KA (INM)

Your future-proof Ka-band system for Inmarsat Global Xpress®
- available in 4.5W and 9W

COBHAM
SATCOM
Connecting the future

Product Sheet



Unlock the power to optimise delivery and performance of broadband for business applications, vessel operations and crew welfare, in any maritime environment with the new SAILOR 1000 XTR Ka; the most advanced 3-axis stabilized antenna system for the Inmarsat Global Xpress® satellite network.

A FUTURE-PROOF GX-R2 PLATFORM

Integrating the best of SAILOR VSAT Technology and SAILOR XTR™, the new cutting-edge technology platform at the heart of all next generation SAILOR antenna systems, SAILOR 1000 XTR Ka represents the state-of-the-art for leveraging the full capabilities of Inmarsat Global Xpress® today, and tomorrow.

The SAILOR 1000 XTR Ka's advanced RF package with new Ka-band transceiver (XCVR) and feed horn supports dual-polarisation and wide-band Ka, making it ready to take advantage of Inmarsat's future GX satellite constellations. It also features sophisticated Tracking Receiver technology to ensure fast

satellite acquisition at start-up and after blockages caused by e.g. atmospheric conditions or vessel superstructure.

FEATURE RICH, QUICK & EASY TO DEPLOY

SAILOR 1000 XTR Ka utilises sophisticated Rapid Deployment Technology to reduce installation complexity and cost. This is a combination of mechanical and software elements such as a true one-cable solution, Dynamic Motor Brakes, the XTR™ Installation Wizard enabling quick and trouble-free deployments.

Technical features include the new XTR Antenna System Control Module located inside the Above Deck Unit (ADU) with a lightning-fast processor, enabling new modular star network component topology, deep self-diagnostics capabilities and extended, highly secure remote access contribute to optimise every aspect of operation and management of SAILOR XTR™ antennas. Further developments include IoT protocols providing on-demand antenna health and performance data, and unique 'in-dome' Ethernet for simple integration of third-party devices such as cellular.

ONE PLATFORM FOR ALL ANTENNAS

- **Rapid deployment technology** - true one-cable, software-controlled solution
- **Best-in-class RF performance** - end-users get more value from their investment
- **Powerful new controller and motors** – improved performance on all levels
- **Built-in flexibility** - ready to deliver now and on future Inmarsat GX constellations
- **Dual antenna operation** - reliable automatic switching between two antennas
- **New secure software platform** - protects against cyber security risks
- **New lighter pedestal design** - simplicity improves mechanical performance
- **Easy servicing and operation** – enable higher QoS and business continuity

SAILOR® 1000 XTR KA (INM)



SPECIFICATIONS

Reflector size	103 cm / 40.6"
Type approvals	Inmarsat
Certification	Compliant with CE (Maritime), ETSI, FCC
System power supply range	100-240 VAC, 50-60 Hz
Antenna system power consumption	4.5W: 135W typ. 185W max. 9.0W: 180W typ. 215W max.

FREQUENCY BAND

Rx	17.7 to 20.2 GHz
Tx	27.5 to 30.0 GHz

ANTENNA CABLE

BDU to ADU cable	Coax cable (50 Ω) for Rx, Tx, MoCA and DC power on a single cable
ADU cable connector	Female N-Connector (50 Ω)
BDU cable connector	Female N-Connector (50 Ω)

SAILOR XTR ABOVE DECK UNIT (ADU)

Antenna type, pedestal	3-axis stabilized tracking antenna with integrated GNSS supporting GPS, GLONASS and Beidou
Antenna type, reflector system	Reflector/sub-reflector, ring focus
Transmit Gain	47.4 dBi typ. @ 29.5 GHz (incl. radome)
Receive Gain	43.5 dBi typ. @ 19.7 GHz (incl. radome)
System G/T	20.9 dB/K typ. @ 19.7 GHz, at ≥10° elevation and clear sky (incl. radome)
GX-R2 transceiver output power EIRP	4.5 Watt or 9 Watt 4.5 W: ≥54.1 dBW (incl. radome) 9.0 W: ≥57.1 dBW (incl. radome)
LNB	Inmarsat GX-R2 transceiver
Polarisation	Circular (RHCP, LHCP) independent controlled for Rx and Tx
Tracking Receiver	Internal "all band/modulation type" including e.g. power, DVB-S2X, GSC and modem RSSI
Satellite acquisition	Automatic - with Gyro/GPS Compass input. Support for gyro free operation.
Elevation Range	-20° to +120°
Cross Elevation	-37° to +37°
Azimuth range	Unlimited (Rotary Joint)
Ship motion, angular	Roll ±30° (6 sec), Pitch ±15° (5 sec), Yaw ±10° (8 sec)
Ship, turning rate and acceleration	15°/S and 15°/S2
ADU motion, linear	Linear accelerations ±2.5 g max any direction
Vibration, operational	Sine: EN60945 (8.7.2), DNV 2.4A, MIL-STD-167-1 (5.1.3.3.5). Random: Maritime
Vibration, survival	Sine: EN60945 (8.7.2) dwell, MIL-STD-167-1 (5.1.3.3.5) dwell. Random: EN60721-3-6 class 6M3 mod. by EN60721-4-6
Shock	EN60721-3-6 class 6M3 mod. by EN60721-4-6. MIL-STD-810F 516.5 (Proc. II)
Temperature (ambient)	Operational: -25°C to +55°C / -13°F to +131°F Storage: -40°C to +85°C / -40°F to +185°F
With SAILOR Smart heater option:	
P/N: 407090-001	Operational: -55°C to +55°C / -67°F to +131°F
Humidity	95%, condensing
Rain / IP class	EN60945 Exposed / IPx6
Wind	80 knots operational, 110 knots survival
Ice, survival	25 mm / 1"
Solar radiation	1120 W/m2 to MIL-STD-810F 505.4
Compass safe distance	1.5 m / 3.3 lb to EN60945
Maintenance, scheduled	None
Maintenance, unscheduled	All modules, motor, RF parts and belts are replaceable through service hatch
Built In Test	Power On Self-Test, Person Activated Self-Test and Continuous Monitoring w. error logging
Dimensions	Height: H 150 cm / 58.9" Diameter: Ø 130 cm / 51.3"
Weight	105 kg / 231 lb

SAILOR XTR BELOW-DECK UNIT (BDU)

Dimensions	1U 19" Rack Mount HxWxD: 4.4 x 48 x 33 cm / 1.75" x 19" x 13"
Weight	3.6 kg / 8 lb
Temperature (ambient)	Operational: -25°C to +55°C / -13°F to +131°F Storage: -40°C to +85°C / -40°F to +185°F
Humidity	EN60945 Protected, 95% (non-condensing)
IP class	IP30
Compass safe distance	0.3 m / 0.7" to EN60945
Interfaces	1x N-Connector for antenna RF Cable (50 Ω) with automatic cable loss compensation 2 x F-Connectors (75 Ω) for Rx & Tx to VSAT modem 1 x Ethernet Data (VSAT Modem Control) 2 x Ethernet (User) 1 x Ethernet (Remote access) 1 x Ethernet for Service and Configuration 1 x RJ-45, RS-422 Data (VSAT Modem Control) 1 x RJ-45, RS-232 Data (VSAT Modem Control) 1 x RJ-45, NMEA 0183 (RS-422 / RS-232) for Gyro/GPS Compass and external GPS input 1 x RJ-45, 4 x General purpose GPIO, Tx mute and Rx lock. 1 x Universal AC power input 1 x Grounding bolt
User interface	Webserver, OLED display (red), 5 pushbuttons, 3 discrete indicator LEDs and On/Off switch, TX Mute and Modem Lock indicator
Temperature control	Built-in fan
No transmit zones	Programmable, 8 zones with azimuth and elevation Real-time blocking map recorder
Remote management and IoT	HTTPS, SSH, Telnet, SNMP Traps, Syslog, CLI, Diagnostic, Statistic, RESTful, MQTT

VSAT MODEM SUPPORT

Modem protocols	Generic, OpenAMIP, OpenBMIP
Modem hardware	SAILOR GX Modem

SAILOR GX MODEM UNIT (GMU)

Dimensions	1U 19" Rack Mount HxWxD: 4.4 x 48 x 33 cm / 1.75" x 19" x 13"
Weight	3.5 kg / 7.7 lb
Humidity	EN60945 Protected, 95% (non-condensing)
IP class	IP30
Compass safe distance	0.3 m / 0.7" to EN60945
Interfaces	2 x F-Connectors (75 Ω) for Rx and Tx to BDU 1 x RJ-45 Ethernet for control and user data, routes through BDU 1 x RS-422 (Modem Control) 1 x RS-232 Data (Modem Control) 1 x RS-232 Modem console 1 x Universal AC power input 1 x Grounding bolt
Input power	100-240 VAC, 50-60 Hz, 90 W peak, 30 W typical
Modem interface control	OpenAMIP, OpenBMIP, RS-422 and RS-232
User interface	Web MMI, On/Off switch and power LED
Temperature control	Built-in fan and heater



Mackay Marine – High Seas
+1 281 479 1515 marinesales@mackaymarine.com
Mackay Communications, Satellite Solutions
+1 919 850 3100 satserv@mackaycomm.com
Mackay Marine Canada
+1 902 469 8480 sales.canada@mackaymarine.com
Mackay Marine Alaska & Pacific Northwest
NWsales@mackaymarine.com Ballard/AK: 206 282 8080
South Seattle/Tacoma: 253 922 6260

Subject to change without further notice.

For further information please contact: satcom.maritime@cobhamsatcom.com