



# Simrad R5000

Simrad R5000 radar systems are available in a range of configurations to meet the requirement for an IMO type-approved X/S-Band radar system aboard CAT 1(H) and CAT 2(H) SOLAS vessels. A modular design makes it easy to create a single or multi-radar system for commercial vessels of any size and type.



▲ **NEW** R5000

## Easy to Learn and Operate

Our R5000 systems are designed for ease of use, and feature a modern interface with intuitive keypad and trackball controls. Widescreen displays give operators constant access to key information, alerts, and settings without distracting from the central PPI. The same interface is used across our complete series of X-Band and S-Band solutions, offering a consistent experience for operators of multi-radar systems.

## Simple and Flexible Installation

Each of our modular systems is based on the R5000 radar processor: a high performance 'black-box' system that connects to the radar transceiver via a thin and easy-to-route Ethernet cable. Multiple R5000 processors can be networked together to create multi-radar systems, and to provide access to radar from multiple stations. Any networked station can control any connected radar system, offering both flexibility and redundancy.

## Type-Approved X-Band Radar Solutions

X-Band radar delivers high-resolution coverage with optimal target separation. We offer type-approved X-Band radar solutions for use aboard CAT 1 and CAT 2 SOLAS vessels, including high speed craft (HSC). Choose from a 12 or 25 kilowatt up-mast transceiver for simple and cost-effective installation, or a 25-kilowatt down-mast transceiver for enhanced serviceability and resistance to harsh environmental conditions. Open array antennas are available in 6, 9, and 12-foot diameters to suit a variety of operational requirements and vessel sizes.

## Type-Approved S-Band Radar Solutions

S-Band radar serves as a secondary system aboard SOLAS vessels of 3,000 GT and above, and offers superior target detection to X-Band radar in poor weather conditions such as rain or fog. We offer IMO type-approved S-Band radar

solutions for use aboard CAT 1 and CAT 2 vessels, including high speed craft (HSC). A lightweight 12-foot open array antenna is paired with a 30-kilowatt S-Band transceiver; the transceiver is available in an up-mast configuration for simple and cost-effective installation, or down-mast configuration for enhanced serviceability and resistance to harsh environmental conditions.

## FEATURES

- Solutions available to suit CAT 1 (H) and CAT 2 (H) SOLAS vessels
- Modern user interface with intuitive keypad and trackball controls
- 24 and 27-inch widescreen display options (category dependent)
- Modular system for ease of installation
- Create multi-radar and multi-station systems

### X-Band

- X-Band radar offers high resolution and optimal target separation
- 6, 9, and 12-foot open array antennas are available to suit a range of vessels
- Choose from a 12 or 25 kW up-mast transceiver, or 25 kW down-mast option

### S-Band

- S-Band radar offers superior target detection to X-Band in harsh weather conditions
- Lightweight 12-foot open array antenna
- 30 kW up-mast or down-mast transceiver

## SPECIFICATIONS

	M5024	M5027
IMO Display category	CAT 2(H)	CAT 1(H)
TFT Active Matrix Panel diagonal (inch)	24	27
Native resolution (pixels)	1920 x 1080	
Screen glass	Anti-reflective and anti-fingerprint coating, optically bonded	
<b>RADAR DISPLAY FEATURES</b>		
Minimum Range (m)	< 40	
Range discrimination (m)	< 40	
Range Accuracy (m)	1% of the maximum range of the scale in use or 30m, which is the greater	
Bearing Discrimination (Deg)	2.3 (6X), 1.5 (9X), 1.2 (12X), 2.3 (12S)	
Bearing Accuracy (Deg)	< 1	
Azimuth on-screen resolution (Deg)	0,1	
<b>RADAR PRESENTATION</b>		
Relative Motion (RM)	Head Up, Course Up and North Up	
True Motion (TM)	Course Up and North Up	
Off-centering	Up to 75% of range scale in use	
Cursor	Polar and Geographical coordinates, continuously displayed when cursor is activated	
<b>TARGET TRACKING (TT)</b>		
Tracking acquisition in background	Automatic, up to 2500 targets within 24NM	
Presentation	Manual/Automatic, up to 100 targets	
<b>TARGET AIS</b>		
AIS Capacity	Up to 6000 receivable target messages	
Display Capacity	Totally 300 target capacity, of which all of 300 can be activated. AIS overflow mechanism of priority	
<b>I/O INTERFACES</b>		
VDR	DVI-D output to VDR. (Same resolution as Monitor output)	
Serial Ports	2 x IEC 61162-2 (AIS, GYRO) 4 x IEC 61162-1 (BAM input, GNSS, LOG)	
Ethernets	3 x RJ45 Ports at 100Mbps	
USB	2 x USB 2.0	

	X-BAND	S-BAND	
Nominal peak power (kW):	12 or 25 up-mast, 25 down-mast	30 up-mast and down-mast	
Operating frequency (MHz):	9410 ± 30	3050 ± 30	
Pulse length (ns):	60 (25kW, 30Kw) 80 (12kW) – 250 – 800		
PRF (with 3 alternative PRF sets) (Hz)	3000 (3040, 2900, 3100) – 1500 (1520, 1450, 1550) – 750 (760, 725, 775)		
Modulator:	MOSFET technology		
IF amplifier:	Logarithmic		
IF bandwidth (MHz):			
- short pulse:	24		
- medium pulse:	5		
- long pulse:	2		
Overall noise figure (nominal dB):	< 5 dB nominal		
Sector blanking:	Two different sectors to be set at time of installation		
<b>ENVIRONMENTAL</b>			
Relative wind velocity	100 knots wind tunnel test at 20 RPM (According to IEC 62388)		
	6 ft CRX-Band	9 ft CRX-Band	12 ft X-Band
			12 ft S-Band
Antenna type	End-fed-slotted wave guide		
Polarization	Horizontal		
Antenna length/swing circle (ft/mm)	6 / 1800	9 / 2650	12 / 3618
Gain (dB)	≥ 29	≥ 31	≥ 32.5
Horizontal beam width at -3 dB	1.3°	0.9°	0.7°
Vertical beam width at -3 dB	22°	22°	22°
Horizontal side lobes (dB):			
- within 10°	- 27	- 27	- 27
- outside 10°	- 30	- 30	- 30
VSWR	Lower than 1.20		
Rotation speed (RPM):			
- Standard	> 20 and > 40	> 20	> 20
- HSC	> 40	N/A	> 40
Maximum Wind resistance (knots)	100		
De-Icer	Optionally available as unit upgrade heater kit		



## GLOBAL SERVICE



Our Service and Support hotlines are available 24/7/365.

### Comes with:

- 2 Year Warranty
- Extended Warranty Options
- Global Service Network
- 2 Year OnBoard Support\*
- 24 Hour Replacement\*

\*Applies to certified vessels only

DISTRIBUTED BY



**Mackay Marine – High Seas**  
+1 281 479 1515 marinesales@mackaymarine.com

**Mackay Communications, Satellite Solutions**  
+1 919 850 3100 satserv@mackaycomm.com

**Mackay Marine Canada**  
+1 902 469 8480 sales.canada@mackaymarine.com

**Mackay Marine Alaska & Pacific Northwest**  
NWsales@mackaymarine.com Ballard/SEA, WA +1 206 282 8080  
Dutch Harbor, AK +1 253 922 6260

**SUPPORT** ▶ Navico Americas +1 918 438 8669 / 855-241-3598 (Toll free)  
Navico Asia Pacific +64 9 925 4595  
Navico EMEA +31 786 530 004

**SALES** ▶ Navico Americas +1 832 377 9578 sales.americas@navico.com  
Navico Asia Pacific +64 9 925 4500 sales.apacnz@navico.com  
Navico EMEA +44 1794 510 010 sales.emea@navico.com

