



Marine Electronics &
Satellite Communications



LT-4200L SATELLITE COMMUNICATIONS SYSTEM

IRIDIUM CERTUS® 200 LANDMOBILE (FIXED INSTALLATION)

FIXED INSTALLATION



LT-4200L IN SHORT

- 3 x Voice Channels (high quality)
- IP-data: 176 kbps (up) / 176 kbps (down)
- High-performance GNSS/GPS receiver
- Single antenna cable solution (up to 150 m)
- Support for external SIP PABX and SIP handsets (up to 8)
- Firewall and user authentication for high level of security
- Web server for configuration and maintenance

PRODUCT DESCRIPTION

The LT-4200L Satellite Communications System (Iridium Certus® 200) is a LandMobile satellite communication product from Lars Thrane A/S. The LT-4200L system is designed for fixed installation only. The LT-4200L system has voice and data capabilities with 100% global coverage provided by the Iridium® Network. The LT-4200L system consists of a control unit, antenna unit, handset, and cradle. The LT-4200L system offers 3 high quality voice channels, and IP-data 176 kbps (up) / 176 kbps (down), making it the perfect satcom communication product for any fixed installation.

PRODUCT FEATURES

VOLUME CONTROL

Handset speaker volume control button

RINGER

Incoming call ringer

MICROPHONE

High-quality microphone

COLOR DISPLAY

Large 4.3" TFT display supporting brightness adjustment and day/night mode themes

KEYPAD


Responsive keypad with brightness adjustments

AUDIO SPEAKER

Audio speaker supporting key beep, voice prompt, and alarms

FUNCTIONAL KEYS

Functional keys; off-hook, on-hook, navigation, and soft keys



INTERFACES

ETHERNET

Ethernet LAN (RJ45). Connectivity for data, Voice (SIP), service and maintenance

CHASSIS GROUND

Chassis ground connector

ANTENNA

Coaxial type-N conn (female). One cable solution supporting power and communication to the antenna

SIM CARD

SIM card behind rubber dust cover for easy insertion and replacement

AUXILIARY

Auxiliary (10-pin) supporting RS-422, and external ringer

POWER

24 VDC



INSTALLATION OPTIONS

ANTENNA MOUNTING KITS




Pole Mount (2.0", Ø53.0mm, A4 Stainless), Antenna Unit

CONTROL UNIT MOUNTING KITS




Bracket Mount Control Unit



Flush Mount Control Unit

SYSTEM CONFIGURATION



SPECIFICATIONS

LT-4200L SATELLITE COMMUNICATIONS SYSTEM

Certification & standards	CE, FCC, ISED, RED, RoHS 2, Iridium®
Vibration, operational	IEC 60945
Vibration, shock	Half sine 20 g/11 ms
Compass Safe Distance, std.	0.3 - 1.4 m (1.0 - 4.6 ft)
Compass Safe Distance, steer.	0.3 - 0.9 m (1.0 - 3.0 ft)
Power consumption: Transmit, max	154 W
Power consumption: Receive	24 W

LT-4210 Control Unit





Weight	0.67 kg (1.48 lbs)
Dimensions	224.0 x 120.0 x 70.0 mm (8.82 x 4.72 x 2.76 in)
Temperature, operational	-15°C to +55°C (+5°F to +131°F)
IP rating, dust and water	IP32
Interfaces	Ethernet, auxiliary, DC input, chassis ground Antenna Unit (N conn.), handset, SIM card
Input power	24 VDC (8 A)

LT-3120 Handset Unit

Weight (handset + wire)	0.30 kg (0.66 lbs)
Dimensions	52.8 x 208.8 x 38.2 mm (2.08 x 8.22 x 1.50 in)
Temperature, operational	-15°C to +55°C (+5°F to +131°F)
IP rating, dust and water	IP32

LT-4230L Antenna Unit

Weight	3.70 kg (8.16 lbs)
Dimensions	238.7 x Ø 224.6 mm (9.40 x Ø 8.84 in)
Temperature, operational	-40°C to +55°C (-40°F to +131°F)
IP rating, dust and water	IP67
Interfaces	Control Unit (N conn.)
Antenna communication cable	Coaxial cable, up to 150 m (500 ft)
Warranty	2 years
Maintenance	None



IN THE BOX

LT-4210 Control Unit	P/N: 51-102664
LT-3120 Handset	P/N: 51-100988
LT-3121 Cradle	P/N: 51-101181
LT-4230L Antenna Unit (LandMobile)	P/N: 51-103149
Bracket Mount, Control Unit	P/N: 91-100771
Power Cable, 3m	P/N: 91-102118
User & Installation Manual	P/N: 95-102665

ACCESSORIES

Flush Mount, Control Unit	P/N: 91-100772
Pole Mount (2.0" pipe, Ø53.0mm, A4 Stainless), Antenna Unit	P/N: 91-102967
Auxiliary Cable, 3m	P/N: 91-100768
Coaxial Cable Ø10.3mm (up to 150m)	
Crimping Tool for Coaxial Cable Ø10.3mm	



Lars Thrane A/S
Skovlytoften 33
DK-2840 Holte, Denmark
Phone: +45 88 30 10 00 Fax: +45 88 30 10 09
Email: sales@thrane.eu
CVR DK-36042443
www.thrane.eu