

SAILOR® 100 XTR TVRO

For the ultimate TV experience at sea
Available as TV for Ku-band and TVHD for Ku- & Ka-band

Product Sheet

**COBHAM
SATCOM**
Connecting the future

Mackay
Marine Electronics &
Satellite Communications
www.mackaymarine.com



Built on decades of continuous research and development, the new SAILOR XTR TVRO combines the field-proven reliability and RF performance of Sea Tel satellite television systems with the rapid deployment technology, unmatched uptime and ultimate serviceability of the new SAILOR XTR platform. With the new SAILOR XTR TVRO line, you will never miss the breaking news or that vital match-winning moment again.

Industry leading performance

Enhanced pointing accuracy, incredible satellite tracking, unique blocking zones capabilities and improved radar immunity, as well as the best Ku Band or Direct TV Ka Band coverage available today ensure SAILOR XTR TVRO delivers an incredible viewing experience, whether stationary or on the move. Electronic band switching maintains seamless coverage when transiting between satellite TV regions too.

Unmatched serviceability

With fewer antenna modules than any other TVRO in the market, the new SAILOR XTR TVRO line offers simplified and streamlined servicing. Rapid Deployment Technology ensures fast and hassle-free roll-out, accelerating operational readiness on single vessels or across entire fleets while maintaining the highest reliability factor. Full IP integration – an industry-first innovation – optimizes serviceability further and accelerates time to fix.

Full portfolio available now

The SAILOR XTR TVRO line is part of a complete satellite TV portfolio for all vessel types, including 1m Ku and Ku-Ka TVHD antennas as well as the 1.2m Ku and the unique, industry first 1.2m Ku-Ka TVHD antenna joining existing 2.4m and 3.7m systems.

SAILOR® XTR™ – One platform for all antennas

- **Enhanced serviceability** with unique IP integration opportunity for easy diagnosis for quick and remote problem solving
- **Electronic switchable feed** seamlessly switches between Linear and Circular Ku Band for full flexibility when changing between regions or services
- **Superior RF performance for maximum footprint coverage** delivers high availability of services globally and an incredible viewing experience at all times
- **Built-in Satellite Library** with over 60 satellite TV profiles to choose from and the ability to create or modify new satellite profiles
- **Simplified hybrid and remote connectivity** including an industry-first built in ethernet port to enable 3rd party devices such as a cellular or other Wi-Fi device.

SAILOR® 100 XTR TVRO

For the ultimate TV experience
Available as TV for Ku-band and TVHD for Ku- & Ka-band



SYSTEM SPECIFICATIONS

Reflector size	103 cm / 40.5"
Certification	Compliant with CE (Maritime), ETSI
System power supply range	100 - 240 VAC, 50-60 Hz
Total system power consumption	50 W typical, 80 W max

FREQUENCY BAND

	Ku-band	Ka-band
TV	10.7 to 12.75 GHz	N/A
TVHD	10.7 to 12.75 GHz	18.3 to 18.8 GHz, 19.7 to 20.2 GHz

ANTENNA CABLE & CONNECTORS

ADU to BDU & Multi-switch cables	Five 75 Ω cables with F-Connectors
Antenna connections	One 50Ω N-Connection for Antenna Control Four 75Ω F-Connections Two 50Ω to 75Ω adapters for Antenna Control Connections included. (ADU-BDU)

ABOVE DECK UNIT (ADU)

Antenna type, pedestal	3-axis (plus auto skew) stabilized tracking antenna with integrated GNSS supporting GPS, GLONASS and Beidou	
Antenna type, reflector system	Reflector/sub-reflector, ring focus	
Minimum EIRP	Ku-band:	Ka-band:
TV	41.5 dBW	N/A
TVHD	41.5 dBW	45 dBW
LNB Type		
TV	Ku-band: Dual-band worldwide programmable	
TVHD	Ku-band only: Dual-band worldwide programmable Ku/Ka-band: Dual-band programmable and DIRECTV	
Polarization	Linear / Circular selectable	
Skew control	Automatic	
Tracking receiver	Internal "all band/modulation type" including e.g. Power and DVB-S2X	
Satellite acquisition	Automatic, with and without Gyro/GPS Compass input	
Satellite verification	NID or DSS	
Stabilization accuracy	Peak error $\lt;0.2^\circ$ under specified ship motion	
Elevation range	<math>-20^\circ< <math>+120^\circ<="" math>="" math><="" td="" to=""> </math>-20^\circ<>	
Cross elevation	$\pm 37^\circ</math>$	
Azimuth range	$680^\circ</math>$	
Ship motion, angular	Roll $\pm 30^\circ</math> (in 6 sec.), Pitch \pm 15^\circ</math> (in 6 sec.), and Yaw \pm 10^\circ</math> (in 6 sec.)$	
Ship, turning rate and acceleration	$15^\circ/s</math> and 15^\circ/s^2</math>$	
ADU motion, linear	Linear accelerations $\pm 2.5 g</math> max any direction$	
Vibration, operational	Sine: EN 60945 (8.7.2)	
Vibration, survival	Sine: EN 60945 (8.7.2) dwell	
Temperature (ambient)	Operational: $-25^\circ C</math> to +55^\circ C</math> / -13^\circ F</math> to +131^\circ F</math>Storage: -40^\circ C</math> to +85^\circ C</math> / -40^\circ F</math> to +185^\circ F</math>$	
Humidity	95%, condensing	
Rain / IP class	EN 60945 Exposed / IPx6	
Wind	80 knots operational / 110 knots Survival	
Ice, survival	25 mm / 1"	
Solar radiation	1120 W/m ² to MIL-STD-810F 505.4	
Compass safe distance	EN 60945	
Maintenance, scheduled	None	
Maintenance, unscheduled	All modules, motor, RF parts and belts are replaceable through service hatch	
Built In Test	Power On Self-Test, Person Activated Self-Test and Continuous Monitoring w. error logging	
Dimensions	Height: H 150 cm / 59" Diameter: \varnothing 130 cm / 51.2"	
Weight	102 kg / 224.8 lbs	

SAILOR XTR BELOW DECK UNIT (BDU)

Dimensions	1U 19 in. rack mount HxWxD: 4.4 x 48 x 33 cm / 1.73 x 18.9 x 13 in.
Weight	3.6 kg / 8 lb
Temperature (ambient)	Operational: $-25^\circ C</math> to +55^\circ C</math> / -13^\circ F</math> to +131^\circ F</math>Storage: -40^\circ C</math> to +85^\circ C</math> / -40^\circ F</math> to +185^\circ F</math>$
Humidity	EN 60945 Protected, 95% (non-condensing)
IP class	IP30
Compass safe distance	0.3 m / 7" to IECEN 60945
Interfaces	1 x Male N-Connector for antenna control cable (50Ω) 3 x Ethernet (User) 1 x Ethernet (Remote access) 1 x Ethernet on front for Service and Configuration 1 x RJ-45, NMEA 0183 (RS-422 / RS-232) for Gyro/ GPS Compass input and external GPS input 1 x RJ-45, 4 x General purpose GPIO 1 x Universal AC Power Input 1 x Grounding bolt
User Interface	Webserver, OLED display, 5 pushbuttons, 3 discrete indicator LEDs and ON/OFF switch
Temperature control	Built-in fan
Blocking zones	Programmable, 8 zones with azimuth and elevation
Remote management and IoT	HTTPS, SSH, Telnet, SNMP Traps, Syslog, CLI, Diagnostic, Statistic, RESTful, MQTT

