

	MAQ 90	MAQ 60	MAQ 22
FEATURES			
Frequency	87.5-92.5 KHz	57.5-62.5 KHz	20-24 KHz
Verified Detection Distance versus -26 dB target strength	300 M	650 M	1100 M
With RDT	N/A	N/A	1250 M
Verified Detection Distance versus 0 dB target strength	700 M	1000 M	2700 M
With RDT	N/A	N/A	3400 M
Maximum Vessel Speed	12 kts	12 kts	20 kts
Hoist Speed	18 s	18 s	9 s
Sea-chest Requirement	8 inch	8 inch	18 inch
Protective Shield	ABS	ABS	Optional SS
Range Scales: 15 Steps	60-1200 M	80-2200 M	100-6000 M
Pulse Length: 0.2-20ms	✓	✓	✓
Stabilization: Directional	✓	✓	✓
Tilt Control +10° to -45°	✓	✓	✓
Echo Strength Presentation Colour: 8 or 64 Colours	✓	✓	✓
Hoist Control Activation Alarm Automatic on or Manual	✓	✓	✓
Transceiver Transmitters: 64 channels	✓	✓	✓
Transmitters RDT: 256 Channels	N/A	N/A	✓
Receiver: 256 Controls to 32 Channels	✓	✓	✓
Interface with: ITI, GPS, External Synchronization	✓	✓	✓
Programmable tonnage readout	✓	✓	✓
Automatic target tracking	✓	✓	✓
Event marker displays for fish heading and speed	✓	✓	✓
Multi-Language control panels	✓	✓	✓